

For restraining PVC Pipe to Mechanical Joint or Push-On Fittings

- 360° Full contact and support of the pipe wall will not damage or distort pipe.
- Restraint devices produced of high strength ductile iron, machined on CNC equipment to exacting tolerances.
- "Pad To Pad" Feature Visual indicator of correct installation.
- Can be installed on new or existing pipe installations.
- Rated at full rated pressure of PVC pipe, min. 2:1 safety factor.

roducts







Nominal Pipe Size	AWWA C-900/C-905 PVC PIPE		Restraint Rods/Nuts		Clamp Bolts		Approx. Weight/Ibs.
	O.D.	Part No.	No.	Size	No.	Size	weightibs.
4"	4.80	6130-04-C	2	3/4" x 7"	2	5/8" x 4"	8
6"	6.90	6130-06-C	2	3/4" x 7"	2	5/8" x 4"	10
8"	9.05	6130-08-C	2	3/4" x 7"	2	3/4" x4"	15
10"	11.10	6130-10-C	4	3/4" x 7"	2	7/8" x 5"	25
12"	13.20	6130-12-C	4	3/4" x 7"	2	7/8" x 5"	27
14"	15.30	6130-14-C	6	3/4" x 17"	4	7/8" x 7"	55
16"	17.40	6130-16-C	6	3/4" x 17"	4	7/8" x 7"	60
18"	19.50	6130-18-C	8	3/4" x 17"	4	1" x 7"	75
20"	21.60	6130-20-C	8	3/4" x 24"	6	1-1/8" x 10"	115
24"	25.80	6130-24-C	12	3/4" x 24"	6	1-1/8" x 10"	145
30"	32.00	6130-30-C	14	1" x 24"	8	1-1/8" x 10"	330
36"	38.30	6130-36-C	14	1" x 24"	8	1-1/8" x 10"	354

Design and dimensions subject to change without notice.

**WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="https://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>.

United Water Products 5355 Ramona Blvd., Jacksonville, FL 32209 TEL. 877-766-4459 FAX: 877-766-4458 Website: www.unitedwaterproducts.com