

# UNI-FIT<sup>®</sup>

## SERIES 6190

For restraining PVC Pipe Bells  
(Bell and Spigot Joints)

Fast & Economical Restraint of PVC Pipe Bell & Spigot Joints.

Restraint Rings provide 360° full contact and support of pipe wall.

Restraint Rings connected by high strength, low alloy rods/nuts.

For use on **NEW OR EXISTING** PVC Pipe Bells.

Rated at full rated pressure of pipe, 2:1 safety factor.

“Recommended Restrained Lengths of PVC Pipe” calculated at no charge.

Contact factory for details.

Joint Restraint  
for PVC Pipe Bells

Sizes 4" ~ 12"



Sizes 14" ~ 24"



Sizes 30" & 36"



Nominal Pipe Size	AWWA C-900/C-905 PVC PIPE		Restraint Rods/Nuts		Clamp Bolts		Approx. Weight/lbs.
	O.D.	Part No.	No.	Size	No.	Size	
4"	4.80	6190-04-C	2	3/4" x 17"	4	5/8" x 4"	17
6"	6.90	6190-06-C	2	3/4" x 17"	4	5/8" x 4"	19
8"	9.05	6190-08-C	2	3/4" x 17"	4	3/4" x 4"	29
10"	11.10	6190-10-C	4	3/4" x 24"	4	7/8" x 5"	53
12"	13.20	6190-12-C	4	3/4" x 24"	4	7/8" x 5"	57
14"	15.30	6190-14-C	6	3/4" x 30"	8	7/8" x 7"	136
16"	17.40	6190-16-C	6	3/4" x 30"	8	7/8" x 7"	147
18"	19.50	6190-18-C	8	3/4" x 30"	8	1" x 7"	206
20"	21.60	6190-20-C	8	3/4" x 36"	8	1-1/8" x 10"	263
24"	25.80	6190-24-C	12	3/4" x 36"	8	1-1/8" x 10"	406
30"	32.00	6190-30-C	14	1" x 40"	16	1-1/8" x 10"	601
36"	38.30	6190-36-C	14	1" x 40"	16	1-1/8" x 10"	672

Form No. U0045



**United Water Products**  
5355 Ramona Blvd., Jacksonville, FL 32205  
TEL: 877-766-4459 FAX: 877-766-4458  
Website: [www.unitedwaterproducts.com](http://www.unitedwaterproducts.com)

0918