

UNI-FIT[®]

Series 6130

**Joint Restraint for
PVC Pipe/MJ Fittings**

For restraining PVC Pipe to
Mechanical Joint or Push-On
Fittings

- 360° Full contact and support of the pipe wall - will not damage or distort pipe.
- Restraint devices produced of high strength ductile iron, machined on CNC equipment to exacting tolerances.
- "Pad To Pad" Feature - Visual indicator of correct installation.
- Can be installed on new or existing pipe installations.
- Rated at full rated pressure of PVC pipe, min. 2:1 safety factor.



Nominal Pipe Size	AWWA C-900/C-905 PVC PIPE		Restraint Rods/Nuts		Clamp Bolts		Approx. Weight/lbs.
	O.D.	Part No.	No.	Size	No.	Size	
4"	4.80	6130-04-C	2	3/4" x 7"	2	5/8" x 4"	8
6"	6.90	6130-06-C	2	3/4" x 7"	2	5/8" x 4"	10
8"	9.05	6130-08-C	2	3/4" x 7"	2	3/4" x 4"	15
10"	11.10	6130-10-C	4	3/4" x 7"	2	7/8" x 5"	25
12"	13.20	6130-12-C	4	3/4" x 7"	2	7/8" x 5"	27
14"	15.30	6130-14-C	6	3/4" x 17"	4	7/8" x 7"	55
16"	17.40	6130-16-C	6	3/4" x 17"	4	7/8" x 7"	60
18"	19.50	6130-18-C	8	3/4" x 17"	4	1" x 7"	75
20"	21.60	6130-20-C	8	3/4" x 24"	6	1-1/8" x 10"	115
24"	25.80	6130-24-C	12	3/4" x 24"	6	1-1/8" x 10"	145
30"	32.00	6130-30-C	14	1" x 24"	8	1-1/8" x 10"	330
36"	38.30	6130-36-C	14	1" x 24"	8	1-1/8" x 10"	354

Design and dimensions subject to change without notice.



United Water Products
8710 Air Park West Drive, Charlotte, NC 28214
Tel. 401-250-3800
Website: www.unitedwaterproducts.com