

SERIES 6190

For restraining PVC Pipe Bells (Bell and Spigot Joints)

Fast & Economical Restraint of PVC Pipe Bell & Spigot Joints.

Restraint Rings provide 360° full contact and support of pipe wall.

Restraint Rings connected by high strength, low alloy rods/nuts.

For use on **NEW OR EXISTING** PVC Pipe Bells.

Rated at full rated pressure of pipe, 2:1 safety factor.

"Recommended Restrained Lengths of PVC Pipe" calculated at no charge.

Contact factory for details.



Sizes 4" ~ 12"



Sizes 14" ~ 24"



sizes 30" & 36"



Nominal Pipe Size	AWWA C-900/C-905 PVC PIPE		Restraint Rods/Nuts		Clamp Bolts		Approx. Weight/lbs.
	O.D.	Part No.	No.	Size	No.	Size	
4"	4.80	6190-04-C	2	3/4" x 17"	4	5/8" x 4"	17
6"	6.90	6190-06-C	2	3/4" x 17"	4	5/8" x 4"	19
8"	9.05	6190-08-C	2	3/4" x 17"	4	3/4" x 4"	29
10"	11.10	6190-10-C	4	3/4" x 24"	4	7/8" x 5"	53
12"	13.20	6190-12-C	4	3/4" x 24"	4	7/8" x 5"	57
14"	15.30	6190-14-C	6	3/4" x 30"	8	7/8" x 7"	136
16"	17.40	6190-16-C	6	3/4" x 30"	8	7/8" x 7"	147
18"	19.50	6190-18-C	8	3/4" x 30"	8	1" x 7"	206
20"	21.60	6190-20-C	8	3/4" x 36"	8	1-1/8" x 10"	263
24"	25.80	6190-24-C	12	3/4" x 36"	8	1-1/8" x 10"	406
30"	32.00	6190-30-C	14	1" x 40"	16	1-1/8" x 10"	601
36"	38.30	6190-36-C	14	1" x 40"	16	1-1/8" x 10"	672



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



Website: unitedwaterproducts.com